



BrainDumps  
Collection

# Cisco

## 650-474 Exam

**PAISESE - Introducing Cisco Identity Services Engine for System Engineer**

Thank you for Downloading 650-474 exam PDF Demo

You can also try our 650-474 practice exam software

**Download Free Demo**

<https://www.braindumpscollection.com/650-474.html>

**DEMO  
VERSION**

(LIMITED CONTENT)

**Questions  
& Answers**

---

**Question: 1**

---

Which statement about Cisco Identity Services Engine high availability is true?

- A. Monitoring nodes are deployed in an active/active mode. One node serves as primary. All logs are sent automatically to both HA monitoring nodes.
- B. Administration nodes are limited to two and are deployed in an active/standby mode.
- C. Secondary Administrative node automatically becomes primary in the event of primary node failure.
- D. Monitoring nodes are deployed in an active/standby mode. All logs sent to the primary are replicated to the secondary node.
- E. Users are served from the secondary Monitoring node only if the active Monitoring node fails.

---

**Answer: D**

---

---

**Question: 2**

---

Which types of design are required in the Cisco ISE ATP program?

- A. schematic and detailed
- B. preliminary and final
- C. high-level and low-level designs
- D. top down and bottom up

---

**Answer: C**

---

---

**Question: 3**

---

Each node can have a different persona and associated services with that persona. Which persona cannot run with other personas on the same Cisco Identity Services Engine node?

- A. Inline Policy Service
- B. Administration
- C. Monitoring
- D. Policy Service

---

**Answer: A**

---

---

**Question: 4**

---

Which external identity sources are not supported on Cisco ISE 1.0?

- A. Sun ONE LDAP Directory Server
- B. Microsoft Active Directory

- C. RSA Authentication Manager
- D. Novell NDS

---

**Answer: D**

---

---

**Question: 5**

---

Which two roles can be deployed across more than two nodes in an instance? (Choose two.)

- A. Monitoring
- B. Administration
- C. Inline Posture
- D. Pokey Service

---

**Answer: AB**

---

---

**Question: 6**

---

Which RADIUS extension is required for posture and profiling support?

- A. ARAP
- B. VSA
- C. CoA
- D. EAPOL

---

**Answer: C**

---

---

**Question: 7**

---

Which methods can be used to create usernames?

- A. general or random
- B. RFC2381or IEEE 1493
- C. Knopf or WS naming
- D. manual or Ruby

---

**Answer: A**

---

---

**Question: 8**

---

Which option is the default authentication priority on a Cisco switch?

- A. MAB, 802.1X, Web-Auth
- B. 802.1X, MAB, Web-Auth
- C. MAB Web-Auth, 802.1X
- D. 802.1X, Web-Auth, MAB

---

**Answer: B**

---

---

**Question: 9**

---

Which statement about Inline Posture node deployment support is true?

- A. The Inline Posture node is supported on VMware ESX 4.1 but not on earlier versions ESX.
- B. The Inline Posture node is supported on any VMware/ESX/ESXi virtual appliance.
- C. The Inline Posture node is supported on the 1121, 3315, 3355, and 3395 appliance.
- D. The Inline Posture node is supported only on the 3315, 3355, and 3395 appliances.

---

**Answer: C**

---

---

**Question: 10**

---

Which appliance supports Cisco ISE 1.0?

- A. ACS 1120 Appliance
- B. VMWare ESX 3.5
- C. NAC 3390 Appliance
- D. NAC 3355 Appliance

---

**Answer: D**

---

---

**Question: 11**

---

In the Cisco ISE ATP program, what must the sales team submit to begin the sales process?

- A. a new product-hold waiver
- B. high-level and low-level designs
- C. a preliminary design and a request for equipment release
- D. a high-level design and BoM

---

**Answer: B**

---

---

**Question: 12**

---

When determining the number of endpoints for a user base, what is a good ratio for a starting point?

- A. 1-to-1
- B. 2-to-1
- C. 3-to-1
- D. 5-to-1

---

**Answer: C**

---

---

**Question: 13**

---

In a distributed deployment when co-locating the Administrator and Monitoring nodes on one appliance what is the maximum number of supported Policy Service nodes?

- A. 5
- B. 10
- C. 3
- D. 1
- E. 40

---

**Answer: A**

---

---

**Question: 14**

---

By default, which traffic does an 802.IX-enabled switch allow before authentication?

- A. all traffic
- B. no traffic
- C. traffic permitted in the port dACL on Cisco ISE
- D. traffic permitted in the default ACL on the switch

---

**Answer: D**

---

---

**Question: 15**

---

Which two deployment methods are supported with Cisco ISE 1.0 with RADIUS NAC?  
(Choose two.)

- A. Unified Wireless
- B. HREAP - Local Switched
- C. HREAP - Central Switched
- D. Autonomous

---

**Answer: AC**

---

---

**Question: 16**

---

Which function does the Cisco NAC Agent not perform?

- A. Windows updates
- B. launch remediation program
- C. antivirus or antispyware definition updates
- D. Macintosh updates

---

**Answer: D**

---

---

**Question: 17**

---

Which scenario does not support Cisco ISE guest services?

- A. wired NAD with local WebAuth
- B. wireless LAN controller with central WebAuth
- C. wireless LAN controller with local WebAuth
- D. wired NAD with central WebAuth

---

**Answer: B**

---

---

**Question: 18**

---

Which statement about Change of Authorization and Inline Posture node is not true?

- A. Inline Posture node supports Layer 3 mode (router mode).
- B. Inline Posture node supports Layer 2 mode (bridge mode).
- C. All Cisco devices support Change of Authorization.
- D. Inline Posture node is used to provide Change of Authorization functionality on devices that lack native Change of Authorization support

---

**Answer: C**

---

---

**Question: 19**

---

Which option does the Cisco ISE guest service not provide?

- A. support for local WebAuth and central WebAuth
- B. integrated authentication support for guest and nonguest accounts
- C. auto-population of login username for self-service registration
- D. email or SMS with credentials created by Admin registration

---

**Answer: C**

---

---

**Question: 20**

---

Which Cisco ISE node does not support automatic failover?

- A. Inline Posture node
- B. Monitoring node
- C. Policy Services node
- D. Admin node

---

**Answer: D**

---

---

**Question: 21**

---

What is the maximum number of endpoints supported on 3315/3355/3395 providing all Cisco BE services respectively?

- A. 5000/1000/50000
- B. 3000/6000/10000
- C. 2000/4000/8000
- D. 1000/2000/5000
- E. 4000/8000/15000

---

**Answer: B**

---

---

**Question: 22**

---

Which statement is true?

- A. A Cisco ISE Advanced license is perpetual in nature.
- B. A Cisco ISE Advanced license can be installed on top of a Base and/or Wireless license.
- C. A Cisco ISE Wireless license can be installed on top of a Base and/or Advanced license.
- D. A Cisco ISE Advanced license can be used without any Base licenses.

---

**Answer: B**

---

---

**Question: 23**

---

At which OSI layer does WebAuth operate?

- A. Layer 2
- B. Layer 1
- C. Layers 4 and 7 in combination
- D. Layer 3
- E. Layer 4

---

**Answer: C**

---

---

**Question: 24**

---

What is the maximum number of supported endpoints on an appliance in stand-alone mode?

- A. 5,000
- B. 7,500
- C. 10,000
- D. 2,000

---

**Answer: D**

---

---

**Question: 25**

---

Which Cisco ISE deployment models support profiling?

- A. Wireless WPA Enterprise TKIP SSIDs
- B. Inline Posture nodes
- C. Cisco Adaptive Security Appliance
- D. Wireless WPA2 Personal AES SSIDs

---

**Answer: B**

---

---

**Question: 26**

---

In which scenario does Cisco ISE allocate an Advanced license?

- A. guest services with dACL enforcement
- B. endpoint authorization using SGA enforcement
- C. dynamic device profiling
- D. high availability Administrator nodes

---

**Answer: C**

---

---

**Question: 27**

---

Which two configurations are acceptable for base and advanced licenses? (Choose two)

- A. no base licenses, 750 advanced licenses
- B. 1000 base license, 500 advanced licenses
- C. 1500 base license, no advanced license
- D. 250 base licenses, 500 advanced licenses

---

**Answer: BC**

---

---

**Question: 28**

---

Which existing platforms support data migration to Cisco ISE 1.0?

- A. NAC4.X
- B. ACS 4.X
- C. NAC 3.X
- D. ACS 5.X



---

**Answer: A**

---

---

**Question: 29**

---

What is the maximum number of support endpoints supported in a Cisco ISE deployment?

- A. 50 endpoints
- B. 100 K endpoints
- C. 80 K endpoints
- D. 200 K endpoints
- E. 1 Million endpoints

---

**Answer: B**

---

---

**Question: 30**

---

What is the maximum syslog rate for the monitoring node without any drop with appreciable latency?

- A. 500 messages/sec
- B. 1000 messages/sec
- C. 2000 messages/sec
- D. 5000 messages/sec

---

**Answer: B**

---

**Thank You for trying 650-474 PDF Demo**

To try our 650-474 practice exam software visit link below

<https://www.braindumpscollection.com/650-474.html>

## Start Your 650-474 Preparation

Use Coupon "20OFF" for extra 20% discount on the purchase of Practice Test Software. Test your 650-474 preparation with actual exam questions.