



BrainDumps
Collection

HP

HP2-Z12 Exam

HP Servicing HP Networking Products Exam

Thank you for Downloading HP2-Z12 exam PDF Demo

You can also try our HP2-Z12 practice exam software

Download Free Demo

<https://www.braindumpscollection.com/HP2-Z12.html>

DEMO
VERSION

(LIMITED CONTENT)

Questions
& Answers

Question: 1

Which area of the network is considered the backbone?

- A. data center
- B. core
- C. distribution layer
- D. LAN access layer

Answer: B

Explanation:

The core is the backbone of the network, a central or common point where traffic flows between users, their workgroups, and shared resources. Most inter-workgroup traffic flows through the core, so it is important that networking devices located in the core introduce little or no delay (latency). Core switches are usually wire-speed, highly available devices.

Question: 2

Which device forwards network traffic based only on Layer 2 information?

- A. router
- B. switch
- C. hub
- D. firewall

Answer: C

Question: 3

Which switch is specifically designed for networks that require basic connectivity and have little or no IT support?

- A. fixed-port switch
- B. light Layer 3 switch
- C. modular switch
- D. unmanaged switch

Answer: D

Explanation:

Unmanaged switch-A switch that enables Ethernet devices to communicate but does not have a management interface. You simply connect the switch to other devices, and the network is operational. Unmanaged switches are intended for networks that require basic connectivity

and have little or no IT support. They are cost-effective and offer intuitive and simple configuration.

Question: 4

Which HP A Series switches provide Layer 2 functionality and a Web browser interface but no CLI?

- A. HP A5800 Series switches
- B. HP NJ2000G IntelliJack switches
- C. HP A3600-E1 Series switches
- D. HP A3100 Series switches

Answer: B

Explanation:

The HP IntelliJack Switch Series is designed to increase network connections and provide support for legacy analog and digital devices. Deployed at the access layer, these Layer 2 switches are connected to an RJ-45 jack and mounted on the wall. They can be powered by PoE or an optional 48V local power supply. The NJ1000G switch is an unmanaged switch; the NJ2000G switch is a Web-managed switch. The NJ100G and NJ2000G switches provide the following:

Question: 5

Several HP A Series switches are distinguished by a dual-personality (or combo) port. What is an accurate description of this port?

- A. It can accept either Ethernet Base-T cable or fiber optic cable
- B. It can accept either Ethernet Base-T cable or a small form-factor pluggable (SFP) transceiver
- C. It is a pair of ports. One accepts Ethernet Base-T cable and one accepts a small form-factor pluggable (SFP) transceiver. Both can be used simultaneously.
- D. It is a pair of ports. One accepts Ethernet Base-T cable and one accepts a small form-factor pluggable (SFP) transceiver. Only one can be used at a time.

Answer: B

Explanation:

Dual-personality port - this port can be used as either a 10/100/1000 port or a Small Form Factor Port (SFP).

Question: 6

You are troubleshooting a connection on an HP A Series switch that has one LED per-port. You want to know if the port is operating in the wrong duplex mode. How do you use the LED to obtain relevant information?

- A. Click the Mode button until the mode LED is blinking green and then check the port LED.
- B. Click the Mode button until the mode LED is yellow and then check the port LED.
- C. Check if the port LED is blinking, which indicates its duplex status (while its color indicates speed).

D. Check the color of the port LED, which indicates its duplex status (while its blinking indicates speed).

Answer: B

Explanation:

You can use the Mode button to check the duplex mode of each port. Press the button until the Mode LED displays yellow. In Duplex Mode, a Port LED displays green if the port is operating in full-duplex mode (meaning data can be transmitted in two directions simultaneously). The Port LED displays yellow if the port is operating in half-duplex mode (meaning data can be transmitted in one direction at a time).

Question: 7

You are installing an HP A Series switch that requires a backup power supply as well as extra power for Power over Ethernet (PoE) devices. Which device should you connect to this switch?

- A. RPS 1200 A
- B. RPS 1000 A3
- C. RPS 800 A
- D. RPS500 A3

Answer: B

Explanation:

Customers can use one of three RPSs with A Series switches:

RPS 1000 A3

RPS 800 A

RPS 500 A3 In addition to providing redundancy, the RPS 1000 A3 provides additional PoE .

Question: 8

The exhibit shows the Power and seven-segment LEDs of an HP A Series switch. What is the switch's status?



Exhibit:



- A. The switch has member ID 8 in the cluster.
- B. The switch has member ID 8 in the cluster, but its attempt to join the cluster has failed.
- C. The switch has failed the power on self test (POST) with ID 8.
- D. Port number 8 has failed the switch's power on self test (POST).

Answer: C

Explanation:

Switch LED	State	Meaning
Power LED is Blinking Red		
Seven-Segment Display LED	Blinking Number 123456789	Self-test (POST) failed. The LED flashes the test ID of the failed test.

Thank You for trying HP2-Z12 PDF Demo

To try our HP2-Z12 practice exam software visit link below

<https://www.braindumpscollection.com/HP2-Z12.html>

Start Your HP2-Z12 Preparation

Use Coupon “20OFF” for extra 20% discount on the purchase of Practice Test Software. Test your HP2-Z12 preparation with actual exam questions.