



BrainDumps
Collection

HP

HPE6-A44 Exam

HP Scalable WLAN Design and Implementation 8 Exam

Thank you for Downloading HPE6-A44 exam PDF Demo

You can also try our HPE6-A44 practice exam software

[Download Free Demo](#)

<https://www.braindumpscollection.com/HPE6-A44.html>

DEMO
VERSION (LIMITED CONTENT)

Questions
& Answers

Version: 11.0

Question: 1

An administrator adds local administrative accounts to manage the Aruba Mobility Controllers (MCs). Which role should be assigned to an administrator who needs to only generate reports and monitor WLANs and ports?

- A. Location-api-management
- B. Network-operations
- C. Root
- D. AP-provisioning

Answer: B

Question: 2

Refer to the exhibit.

```
Last synchronization time: Thu Apr 13 07:42:48 2017
To Master Switch at 10.254.10.101: succeeded
WMS Database backup file size: 39121 bytes
Local User Database backup file size: 29694 bytes
Global AP Database backup file size: 13375 bytes
IAP Database backup file size: 3750 bytes
Airgroup Database backup file size: 3052 bytes
License Database backup file size: 5358 bytes
CPSec Database backup file size: 3224 bytes
Bocmgr Database backup file size: 6016 bytes
Synchronization took 1 second
```

```
1 synchronization attempted
0 synchronization have failed
Periodic synchronization is enabled and runs every 60 minutes
Synchronization doesn't include Captive Portal Custom data
Airmatch database gets synchronized periodically. Last synchronization time:
2017-04-13 07:22:2019:20:24
```

What can be determined from the command output shown in the exhibit?


- A. The synchronized data is protected by VRRP.
- B. The command was executed on the standby Mobility Master (MM).

- C. The synchronization period is at its default value.
- D. The other Mobility Master (MM) is the active license server.

Answer: D

Question: 3

Refer to the exhibit.



An administrator supports a RAP at a branch office shown in the exhibit. The company has one Mobility Controller (MC) at the Primary DMZ site and one at the Secondary DMZ site. The RAP is configured to connect to only the MC at the Primary DMZ site. A network outage with the ISP at the Primary DMZ site causes the RAP to reboot. Upon reboot, the RAP cannot build a tunnel to the Secondary DMZ site MC because the administrator forgot to add the Second LMS IP address to the AP Group configuration. Once the RAP can successfully connect, the administrator can add the Secondary DMZ MC as a backup LMS to fix the AP Group.

What should the administrator implement to allow the RAP to connect to the MC at the Secondary DMZ site while the outage at the primary site persists?

- A. Dynamic discovery through DHCP Option 43
- B. Static configuration from apboot mode
- C. Dynamic discovery through DHCP Option 60
- D. Dynamic discovery through multicast ADP

Answer: A

Question: 4

An administrator supports a cluster of four Aruba Mobility Controllers (MCs) with management addresses of 10.1.100.101, 10.1.100.102, 10.1.100.103, and 10.1.202.181. The administrator accesses an AP associated with this cluster, reboots it and accesses apboot mode. The administrator executes the printenv command.

Which AP parameter contains the IP addresses of the cluster members that the AP should use to connect to the cluster?

- A. Nodelist
- B. Servername
- C. Master_ip
- D. Cfg_lms

Answer: B

Question: 5

A VIA client tries to initially connect to corporate office controller through an intermediate firewall. However, the VPN connection fails. The administrator examines the firewall rules and determines that rules for UDP 4500 and UDP 500 are configured.

Which additional protocol must be allowed in the firewall rules to resolve this connection failure?

- A. TCP 22
- B. TCP 443
- C. UDP 8200
- D. ESP

Answer: D

Question: 6

An administrator has a cluster of Aruba Mobility Controllers (MCs). The administrator wants to manually reboot one of the controllers.

Before rebooting, which command should the administrator use to move the APs?

- A. apmove
- B. lc-cluster move ap
- C. active-ap-rebalance
- D. active-ap-lb

Answer: B

Question: 7

Which Aruba Unified Communications and Collaboration (UCC) deployment mode should be used when UCC is disabled on the Mobility Controllers (MCs)?

- A. Heuristics mode
- B. WMM mode
- C. ALG mode
- D. SDN-API mode

Answer: B

Question: 8

An administrator implements a ClearPass solution to authenticate Aruba wireless users. The Aruba wireless solution is an ArubaOS 8.x Mobility Master (MM) deployment. ClearPass sends an Aruba VSA role name for an authenticated user. However, the administrator notices that the role assigned to the user is different from the one assigned by the ClearPass server.

Which two items should the administrator verify that might be the cause of this problem? (Choose two.)

- A. Enablement of user roles on the controller
- B. Spelling of the role on the ClearPass server
- C. Server-derived role assignment on the ClearPass server
- D. Role existence on the Managed Network
- E. Order assignment that the controller uses to select a user role

Answer: BD

Question: 9

Refer to the exhibit.

```
hostname "swdi-3810-2"  
module 1 type j1073x  
console idle-timeout 600  
console serial-usb 600  
ip routing  
tunneled-node-server  
  controller-ip 10.1.20.100  
  exit  
interface 1  
  disable  
  exit  
interface 20  
  name "Wireless Client NIC"  
  tunneled-node-server  
  exit  
interface 21  
  disable  
  tunneled-node-server  
  exit  
vlan 23  
  name "VLAN23"  
  untagged 20-21  
  no ip address  
  exit
```

What is true about the configuration shown in the exhibit?

- A. This is an ArubaOS-Switch configured for per-user tunneled node.
- B. This is an ArubaOS controller configured for per-user tunneled node.
- C. This is an ArubaOS-Switch configured for per-port tunneled node.
- D. This is an ArubaOS controller configured for per-user tunneled node.

Answer: C

Question: 10

Which license type must an administrator purchase to use Spectrum Monitoring?

- A. RFP
- B. VMC

- C. PEFV
- D. PEFNG

Answer: A

Reference:

<http://community.arubanetworks.com/t5/Wireless-Access/license-requirements-air-monitorspectrum-monitor/td-p/243832>

Question: 11

A company opens a new branch office and a RAP is used to connect to a corporate office Aruba Mobility Controller (MC). The company needs to provide connectivity to the office across the street. There is an AP across the street. However, there is no wired connectivity between the buildings. Which actions can the administrator select to provide the required connectivity? (Choose two.)

- A. Provision all Aps at the branch office as Mesh Points.
- B. Provision all Aps at the branch offices as Mash Portals.
- C. Implement one of the Aps as a Mesh Point.
- D. Provision the RAP as a Mesh Portal.
- E. Implement two mesh clusters.

Answer: AD

Question: 12

A customer uses an SIP application that is not supported by Aruba United Communications and Collaboration (UCC). Which voice deployment mode should the administrator implement on Aruba Mobility Controllers (MCs) to support this application?

- A. Heuristic mode
- B. SDN-API mode
- C. QoS-mode
- D. WMM-only mode

Answer: A

Question: 13

A company has a wireless network that contains a cluster of four Aruba 7030 Mobility Controllers (MC) managed by a Mobility Master (MM) located in the data center. The company has Aps deployed that are nearing the capacity of the cluster. The administrator wants to increase AP capacity. How can the administrator solve the problem?

- A. Add a new controller to the Mobility Master.
- B. Add a Virtual Mobility Controller to the existing cluster.
- C. Add a 7030 controller to the existing cluster.
- D. Add a 7220 controller to the existing cluster.

Answer: B

Question: 14

An Administrator supports a group of employees that connect to the corporate office using the VIA client. An Aruba Mobility Controller (MC), behind a corporate firewall, terminates the user's VPN sessions. The VPN sessions fail to establish because of the existing firewall rules. Which connections must the administrator allow on the firewall? (Choose three.)

- A. UDP 8202
- B. UDP 4500
- C. UDP 8211
- D. TCP 4443
- E. TCP 443
- F. UDP 500

Answer: ABE

Question: 15

Refer to the exhibit.

 This Device is in monitor-only mode.

Device Info

Status: Down (ICMP ping failed (after SNMP get failed))

Configuration:	Mismatched (The settings on the device do not match the desired configuration policy.)		
Firmware:	6.4.2.3_47524		
Upstream Device:	-	Upstream Port:	-
Controller Role:	Local	Master Controller:	7030-East
Type:	Aruba 7030	Last Contacted:	7/5/2016 6:37 PM EDT
LAN MAC Address:	00:0B:86:B6:13:17	Serial:	CR0006372
Location:	-	Contact:	-
IP Address:	10.2.70.101	APs:	0
VPN Sessions:	-	VPN Usage:	-

Quick Links: [Open controller web UI...](#) 

Under which AirWave Management Platform (AMP) section should an administrator navigate to see the connection status between the AMP and managed device shown in the exhibit?

- A. Folders
- B. Aps/Devices
- C. VisualRF
- D. Device Setup

Answer: B

Thank You for trying HPE6-A44 PDF Demo

To try our HPE6-A44 practice exam software visit link below

<https://www.braindumpscollection.com/HPE6-A44.html>

Start Your HPE6-A44 Preparation

Use Coupon "20OFF" for extra 20% discount on the purchase of Practice Test Software. Test your HPE6-A44 preparation with actual exam questions.