



Fortinet

NSE6_FAZ-7.2 Exam

Fortinet NSE 6 - FortiAnalyzer 7.2 Administrator

Thank you for Downloading NSE6_FAZ-7.2 exam PDF Demo

You can also try our NSE6_FAZ-7.2 practice exam software

Download Free Demo

https://www.braindumpscollection.com/NSE6_FAZ-7.2.html

DEMO
VERSION

(LIMITED CONTENT)

Questions
& Answers

Version: 4.0

Question: 1

Refer to the exhibit.

The screenshot shows the 'Cluster Settings' configuration page for a FortiAnalyzer. The 'Operation Mode' is set to 'High Availability' (selected) and 'Standalone'. The 'Preferred Role' is set to 'Primary' (selected) and 'Secondary'. The 'Cluster Virtual IP' section shows the 'IP Address' as 192.168.101.222 and the 'Interface' as port1. The 'Cluster Settings' section shows the 'Peer IP' as 10.0.1.210 and the 'Peer SN' as FAZ-VM0000065040. The 'Group Name' is NSE6, the 'Group ID' is 1, and the 'Password' is masked with dots. The 'Heart Beat Interval' is 10 seconds, the 'Failover Threshold' is 30, and the 'Priority' is 120. A toggle switch at the bottom is turned off.

Cluster Settings	
Operation Mode	Standalone High Availability
Preferred Role	Secondary Primary
Cluster Virtual IP	
IP Address and Interface	IP Address: 192.168.101.222 Interface: port1
Cluster Settings	
Peer IP and Peer SN	Peer IP: 10.0.1.210 Peer SN: FAZ-VM0000065040
Group Name	NSE6
Group ID	1 (1-255)
Password
Heart Beat Interval	10 Seconds
Failover Threshold	30
Priority	120

The image displays the configuration of a FortiAnalyzer the administrator wants to join to an existing HA cluster.

What can you conclude from the configuration displayed?

- A. After joining to the cluster, this FortiAnalyzer will keep an updated log database.
- B. This FortiAnalyzer will trigger a failover after losing communication with its peers for 10 seconds.
- C. This FortiAnalyzer will join to the existing HA cluster as the primary.
- D. This FortiAnalyzer is configured to receive logs in its port1.

Answer: D

Explanation:

The configuration displayed in the exhibit indicates that the FortiAnalyzer is set up with a cluster virtual IP address of 192.168.101.222 assigned to interface port1. This setup is typically used for the FortiAnalyzer to receive logs on that interface when operating in a High Availability (HA) configuration. The exhibit does not provide enough information to conclude whether this

FortiAnalyzer will be the primary unit in the HA cluster or the duration for the failover trigger; it only confirms the interface configuration for log reception. Reference: Based on the FortiAnalyzer 7.4.1 Administration Guide, the similar configurations for HA and log reception are discussed, which would be relevant for understanding the settings in FortiAnalyzer 7.2.

Thank You for trying NSE6_FAZ-7.2 PDF Demo

To try our NSE6_FAZ-7.2 practice exam software visit link
below

https://www.braindumpscollection.com/NSE6_FAZ-7.2.html

Start Your NSE6_FAZ-7.2 Preparation

Use Coupon "20OFF" for extra 20% discount on the purchase of Practice Test Software. Test your NSE6_FAZ-7.2 preparation with actual exam questions.